Light-fittings

- MIZAR Series Light-fittings for fixed installations -60W
- HYDRA Series Light-fittings for fixed installations -100W
- HALE Series
 Portable lighting 60W



Light-fittings MIZAR Series

■ Light-fittings for fixed installations - 60W

MIZAR Series

For incandescent lamps Thermoplastic diffuser

			BULKHEAD LIGHT
			RECTANGULAR
Lamp power	Lamp holder	Colour	IP44
COM	B22		780.2262 12
60W	E27		780.2762 12

- Thermoplastic diffuser. For continuous use, use the version with polycarbonate diffuser.
- Electric bulb not included.

	MIZAR	Series	
786.		786.	



For incandescent lamps Polycarbonate diffuser

		=	BULKHEA RECTAN	
Lamp power	Lamp holder	Colour	IP44	IP55
60W	B22		781.2261 1/12	786.2261 1/12
		TRANSPARENT	781.2260 1/12	786.2260 1/12
	577		781.2761 1/12	786.2761 1/12
	E27	TRANSPARENT	781.2760 1/12	786,2760 1/12

- Polycarbonate diffuser
- Electric bulb not included.

Light-fittings MIZAR Series



■ Light-fittings for fixed installations - 60W

MIZAR Series
781.



Red bulkhead lights for indicating working areas [E27]

						BULKHEAD LIGHT
IP	Lamp holder	Volt	Cable length	Notes	Colour	RECTANGULAR
			10m	x1 LAMP.		781.2761/1
IP44	E27	24V	10+6m	x2 LAMP.		781.2761/2
			10+6+6+1m	x3 LAMP.		781.2761/3

- Rubber cable, 2x1.5mm².
- Diffuser colour: red.
- Bulb included, E27 25W 24V~.



Distribution assemblies for night-time power supply of lights indicating working areas (art. 630.001 / 630.002)

MIZAR Series

■ Light-fittings for fixed installations - 60W

MIZAR Series

Red bulkhead lights for indicating working areas [LED+BATTERY]

			BULKHEAD LIGHT
IP	Lamp holder	Colour	RECTANGULAR
IP55	LED		786.0100 1/12

- Power supply: four 1.5V "AA" batteries (not included).
- Switching on: automatic with twilight switch.
- Double operation: fixed light and flashing with switch that selects the desired function.

Light-fittings MIZAR Series



■ Light-fittings for fixed installations - 60W

MIZAR Series				
786.				

Red bulkhead lights for indicating working areas [LED]

			BULKHEAD LIGHT		
IP	Lamp holder	Colour	RECTANGULAR		
			786.0200		
IP55	LED		786.0210 2 1/12		
			786.0220 1/12		

- 1 Automatic twilight turn-on. Fixed light.
- 2 Automatic twilight turn-on. Two operation modes: fixed light or flashing light. With mode selector switch.
- 3 Direct turn-on (without twilight turn-on) and fixed light
- With 220V-powered LED flasher.



MIZAR Series light-fittings are fitted with a slot on the rear of the base for hooking onto a nail, screw or hook, or for fastening to poles, pipes, bars or scaffolding using one or two cable ties.

Light-fittings HYDRA Series

■ Light-fittings for fixed installations - 100W

HYDRA Series				
791.	796.			



Bulkhead light ROUND

Version	IP	Lamp power	Lamp holder	BULKHEA	AD LIGHT
	IP44		B22	791.12210 1/6	
DOLLNID	IP 44	10011	E27	791.12710	
ROUND		100W	B22		796.12210 1/6
	IP65		E27		796.12710 ² 1/6

- 1 Lampholder in porcelain
- 2 Lampholder in resin
- Diffuser and shell in polycarbonate.
- Lighting devices for fixed installation
- Steel screws with galvanised anti-rust treatment.
- Reflecting parabola in aluminium.

	-	_	_	_			
HY	m	D.	Δ	8	ri	ρ	c

791.	796.



Bulkhead light SQUARE

Version	IP	Lamp power	Lamp holder	BULKHEAD LIGHT				
	IDAA	- 100W	B22	791.22210 1/6				
COLLADE	IP44		E27	791.22710 ² 1/6				
SQUARE	ince	IUUW	B22		796.22210 II 1/6			
	IP65		E27		796,22710 2 1/6			

- 1 Lampholder in porcelain
- 2 Lampholder in resin
- Diffuser and shell in polycarbonate.
- Lighting devices for fixed installation
- Steel screws with galvanised anti-rust treatment.
- Reflecting parabola in aluminium.

Light-fittings HYDRA Series



■ Light-fittings for fixed installations - 100W

HYDRA Series 791. 796.

Bulkhead light OVAL

Version	IP	Lamp power	Lamp holder	BULKHEAD LIGHT				
	IP44	- 100W	B22	791.32210 🗆	1/6			
OVAL	11744		E27	791.327102	1/6			
OVAL	IP65		B22			796.32210 1/6		
			E27			796.32710 ² 1/6		

- 1 Lampholder in porcelain
- 2 Lampholder in resin
- Diffuser and shell in polycarbonate.
- Lighting devices for fixed installation
- Steel screws with galvanised anti-rust treatment.
- Reflecting parabola in aluminium.

HYDRA Series

790.





Decorative frames

Version	Colour	FRAME						
DOLIND		790.101	1/6					
ROUND		790.102	1/6					
OVAL					790.301	1/6		
OVAL					790.302	1/6		

Light-fittings HALE Series

Portable lighting - 60W

HALE Series
770.

With protective guard and zinc-plated steel reflector

PORTABLE LAMP	
STANDARD LID	HEAVY DUTY
IP20	
60W	
 E27	'
 770 207	24

new Heavy Duty products are especially suited to grevious working conditions and are also resistant to highly salty environments

- Protective guard that can be opened for light bulb replacement.
- Lighting devices with protective guard and zinc-plated steel reflector:
- Handgrip in insulating, non-hygroscopic thermoplastic material with tilting system that prevents the lamp, when placed on a flat surface, to directly irradiate said surface and thus prevent dangerous overheating.
- Tapered cable gland
- Cable gland
- Adjustable hook.
- Rocker switch and screw clamp for cable replacement.
- For lamps up to 60W (incandescent)
- Screw cable stay.
- Cable H05W-F (PVC)



2P+E-16A-(\$17)

Light-fittings HALE Series



Portable lighting - 60W

	HALE Series	
	770.	
5	2	2
	4	-
T	-	
8		-0

With impact-resistant protective diffuser

					PORTABLE LAMP					
					IP65			IP20		
							60W			
Plug	Volt	Cable length	Cable	Cable section			E27			
	250V	5m							770.407 🗆	1/6
		10m							770.408	1/6
IEC309	24V	5m	H05VV-F	2x1mm²			770.405	1/6		
		10m					770.406	1/6		
	2504	5m					770.409	1/6		
	250V	10m					770.410	1/6		
		without cable			770.400	1/6				

- The degree of protection IP20 is due to preserve of plug for domestic use, while the apparatus is IP65; for example, if plugged into a socket in the garage the lamp can be used in the garden.
- Protective shell in collision-proof technopolymer
- Lighting devices with protective shell
- Cable H05RN-F (RUBBER)
- Handgrip in non-hygroscopic technopolymer.
- Cable gland
- Reflecting parabola in aluminium.
- Adjustable hook.
- Rocker switch and screw clamp for cable replacement.
- For lamps up to 60W (incandescent)
- Screw cable stay.